

R134a 5-LAYERS A/C HOSE

A20/A10

5 LAYERS (SAE J2064 TYPE C)



TUBE : BLACK,SMOOTH,SPECIAL SYNTHETIC RUBBER WITH VERY LOW GAS PERMEATION.
 REINFORCEMENT : 2 HIGH TENSILE SYNTHETIC TEXTILE BRAID.
 COVER : SPECIAL SYNTHETIC PIN-PRICKED RUBBER,RESISTANT TO HIGH TEMPERATURE APPLICATIONS.
 APPLICATION : FOR THE TRANSFER OF R134A GAS AND LIQUID,IN AIR CONDITIONING SYSTEMS FOR AUTOMOTIVE INDUSTRY.

TEMPERATURE RANGE : -40°C~+135°C / -40°F~+275°F

PERMEABILITY(KG / M2 / YEAR) 1.6

THICK WALL A20 / THIN WALL A10

TYPE	SIZE		ID (mm)		OD (mm)		Wall Thickness (mm)	WP	BP	BR/r	L
	Dash Size	inch	min	max	min	max	mm	W.P.	B.P.	mm	max/m
C-A20-8	8.2	5/16	7.8	8.6	18.0	19.0	5.2±0.4	3.5	21	70	50/100
C-A20-10.5	10.5	13/32	10.1	10.9	22.5	23.5	6.3±0.4	3.5	21	85	50/100
C-A20-13a	13.0	1/2	12.6	13.4	24.9	25.9	6.2±0.4	3.5	22	85	50/100
C-A20-13b	13.0	1/2	12.6	13.4	22.5	23.5	5.0±0.4	3.5	22	95	50/100
C-A20-16	16.1	5/8	15.7	16.5	28.1	29.1	6.3±0.4	3.5	18	105	50/100
C-A10-8	8.2	5/16	7.9	8.5	14.8	15.6	3.5±0.4	3.5	24	55	50/100
C-A10-10	10.5	13/32	10.2	10.8	18.3	19.1	4.1±0.4	3.5	24	75	50/100
C-A10-11	11.5	7/16	11.2	11.8	18.1	18.9	3.5±0.4	3.8	24	75	50/100
C-A10-13	13.2	1/2	12.9	13.5	20.4	21.2	3.8±0.4	3.8	23	75	50/100
C-A10-15	15.2	5/8	14.8	15.6	22.3	23.3	3.8±0.4	3.8	22	85	50/100
C-A10-19	19	3/4	18.5	19.5	27.9	29.1	4.8±0.4	4.8	24	105	50/100

MARKING/ INK JET

NORMS:	SAE J2064 TYPE C	COLOUR	 BLACK
--------	---------------------	--------	--