

ULTRA-HIGH PRESSURE HOSE

UH-2640D/2640N

6 Steel Wire Spiral







TUBE : DN 4-8: POLYOXYMETHYLENE; DN 12-25: POLYAMIDE.
 REINFORCEMENT : SIX SPIRAL LAYERS OF MAXIMUM TENSILE STEEL WIRE.
 COVER : POLYAMIDE.
 APPLICATION : FOR HYDRODEMOLITION, WATER JET CUTTING, SHIP WASHDOWN AND INDUSTRIAL HIGH-PRESSURE CLEANING.
 TEMPERATURE RANGE : -10°C ~ +70°C / 14°F ~ 158°F
 -HT : -10°C up to +100°C / 14°F ~ 212°F

TYPE	SIZE		ID (mm)		OD (mm)	WP		BP		BR/r	W	L
	Dash Size	inch	min	max	max	bar	psi	bar	psi	mm	g/m	max/m
UH-2640D-04	-025	5/32	11.5	12.5	12.5	2800	40600	7000	101500	140	290	50/100
UH-2640D-05	-03	3/16	12.5	13.5	13.0	2500	36250	6250	90625	175	410	50/100
UH-2640D-06	-04	1/4	14.1	15.1	14.6	2500	36250	6250	90625	200	640	50/100
UH-2640D-08	-05	5/16	16.4	17.4	16.9	2100	30450	5250	76125	225	680	50/100
UH-2640D-13	-8	1/2	12.3	13.3	24.5	1800	26100	4500	65250	290	1360	50/100
UH-2640D-19	-12	3/4	19.1	20.1	33.0	1400	20300	3500	50750	350	2100	50/100
UH-2640D-25	-16	1	24.5	25.5	40.0	1200	17400	300	43500	400	2900	50/100
UH-2640D-19HT	-12	3/4	19.1	20.1	33.0	1100	15950	2750	39875	350	2160	50/100



MARKING / INK JET

NORMS	COLOUR
	   
	YELLOW BLACK RED BLUE